Application No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

inputting and outputting power to and from a residual one shaft, based on predetermined powers input to and output from any two shafts among said three shafts:

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor; and

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft, wherein said braking control means comprises means for enabling said motor to carry out a power operation, thereby applying a braking force to said drive shaft.

5. (Amended) A power output apparatus [in accordance with claim 1,] <u>for outputting power to a drive shaft, said power output apparatus comprising:</u>

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

three shaft-type power input/output means having three shafts respectively linking said engine and said drive shaft, said three shaft-type power input/output means inputting and outputting power to and from a residual one shaft, based on predetermined powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor; and

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft, wherein said braking control means comprises means for locking up said motor.

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

Application No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

three shaft-type power input/output means having three shafts respectively linking said engine and said drive shaft, said three shaft-type power input/output means inputting and outputting power to and from a residual one shaft, based on predetermined powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor;

<u>braking control means for controlling said engine and said motor, based on</u>

<u>a charging state of said storage battery means, in order to enable a braking force to be</u>

<u>applied to said drive shaft;</u>

a second motor for inputting and outputting power to and from said drive
shaft, in addition to said motor working as a first motor, wherein said storage battery
means comprises means for supplying and receiving an electrical energy required for
inputting and outputting power to and from said second motor; and

storage battery means, wherein said braking control means comprises means for controlling said engine, said first motor, and said second motor based on the charging state of said storage battery means detected by said charging state detection means, thereby applying a braking force to said drive shaft, and means for regulating the charging state of

said storage battery means detected by said charging state detection means to be within a predetermined range.

9. (Amended) A power output apparatus [in accordance with claim 6, wherein said braking control means comprises] for outputting power to a drive shaft, said power output apparatus comprising:

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

three shaft-type power input/output means having three shafts respectively

linking said engine and said drive shaft, said three shaft-type power input/output means
inputting and outputting power to and from a residual one shaft, based on predetermined
powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor;

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft; and

shaft, in addition to said motor working as a first motor, wherein said storage battery

means comprises means for supplying and receiving an electrical energy required for
inputting and outputting power to and from said second motor, and said braking control
means comprises means for controlling said engine, said first motor, and said second
motor, in order to enable a braking force to be applied to said drive shaft, and means for
controlling said second motor in order to enable said second motor to apply a braking force

Application No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

to said drive shaft, while controlling said first motor in order to make power input to and output from said first motor equal to zero.

14. (Amended) A power output apparatus [in accordance with claim 6, wherein said braking control means comprises] for outputting power to a drive shaft, said power output apparatus comprising:

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

three shaft-type power input/output means having three shafts respectively

linking said engine and said drive shaft, said three shaft-type power input/output means

inputting and outputting power to and from a residual one shaft, based on predetermined

powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor;

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft; and

a second motor for inputting and outputting power to and from said drive shaft, in addition to said motor working as a first motor, wherein said storage battery means comprises means for supplying and receiving an electrical energy required for inputting and outputting power to and from said second motor, and said braking control means comprises means for controlling said engine, said first motor, and said second motor, in order to enable a braking force to be applied to said drive shaft, and means for controlling said first motor and said second motor, in order to enable an electrical energy

regenerated by said second motor to be identical with an electrical energy consumed by said first motor.

17. (Amended) A power output apparatus [in accordance with claim 16, wherein said braking control means comprises] for outputting power to a drive shaft, said power output apparatus comprising:

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

three shaft-type power input/output means having three shafts respectively
linking said engine and said drive shaft, said three shaft-type power input/output means
inputting and outputting power to and from a residual one shaft, based on predetermined
powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor;

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft;

a second motor for inputting and outputting power to and from said output shaft of said engine, in addition to said motor working as a first motor, wherein said storage battery means comprises means for supplying and receiving an electrical energy required for inputting and outputting power to and from said second motor;

storage battery means, wherein said braking control means comprises means for controlling said engine, said first motor, and said second motor in order to enable a

Application No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

braking force to be applied to said drive shaft based on the charging state of said storage battery means detected by said charging state detection means, and means for regulating the charging state of said storage battery means detected by said charging state detection means to be within a predetermined range.

19. (Amended) A power output apparatus [in accordance with claim 15, wherein said braking control means comprises] for outputting power to a drive shaft, said power output apparatus comprising:

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

three shaft-type power input/output means having three shafts respectively

linking said engine and said drive shaft, said three shaft-type power input/output means

inputting and outputting power to and from a residual one shaft, based on predetermined

powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor;

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft; and

a second motor for inputting and outputting power to and from said output shaft of said engine, in addition to said motor working as a first motor, wherein said storage battery means comprises means for supplying and receiving an electrical energy required for inputting and outputting power to and from said second motor, and said braking control means comprises means for controlling said engine, said first motor, and

Aprication No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

said second motor, in order to enable a braking force to be applied to said drive shaft, and means for controlling said first motor and said second motor, in order to enable an electrical energy regenerated by said second motor to be identical with an electrical energy consumed by said first motor.

Please add new claims 22-25 as follows:

--22. A power output apparatus for outputting power to a drive shaft, said power output apparatus comprising:

an engine having an output shaft;

a motor having a rotating shaft and inputting and outputting power to and from said rotating shaft;

three shaft-type power input/output means having three shafts respectively

linking said engine and said drive shaft, said three shaft-type power input/output means

inputting and outputting power to and from a residual one shaft, based on predetermined

powers input to and output from any two shafts among said three shafts;

storage battery means for supplying and receiving an electrical energy required for inputting and outputting power to and from said motor; and

braking control means for controlling said engine and said motor, based on a charging state of said storage battery means, in order to enable a braking force to be applied to said drive shaft;

a remaining charge detection means that detects the remaining charge of the storage battery means; and

an engine driving means that drives said engine in a predetermined operating condition, which enables said motor to regenerate electric power, when the remaining charge of the battery is less than a predetermined threshold value.--

Anication No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

--23. A method of controlling a power output apparatus, for outputting power to a drive shaft, having an engine with an output shaft, a motor with a rotating shaft, and a three shaft-type power input/output means having three shafts respectively linking said engine and said drive shaft, the method comprising:

inputting and outputting power to and from said rotating shaft;

inputting and outputting power, via the three shaft-type power input/output means, to and from a residual one shaft, based on predetermined powers input to and output from any two shafts among said three shafts;

supplying and receiving an electrical energy, from a storage battery means, required for inputting and outputting power to and from said motor;

controlling, using a braking controlling means, said engine and said motor,
based on a charging state of said storage battery means, in order to enable a braking force
to be applied to said drive shaft, and

enabling said motor to carry out a power operation, thereby applying a braking force to said drive shaft by means of said braking control means.--

--24. A method of controlling a power output apparatus, for outputting power to a drive shaft, having an engine with an output shaft, a motor with a rotating shaft, and three shaft-type power input/output means having three shafts respectively linking said engine and said drive shaft, a second motor, the method comprising:

inputting and outputting power to and from said rotating shaft;

inputting and outputting power, via said three shaft-type power input/output
means, to and from a residual one shaft, based on predetermined powers input to and
output from any two shafts among said three shafts;

Aprication No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

supplying and receiving an electrical energy, from a storage battery means, required for inputting and outputting power to and from said motor;

controlling, using a braking control means, said engine and said motor,

based on a charging state of said storage battery means, in order to enable a braking force
to be applied to said drive shaft;

inputting and outputting power to and from said drive shaft via the second motor, in addition to said motor working as a first motor;

supplying and receiving an electrical energy, from said battery storage
means, required for inputting and outputting power to and from said second motor;

detecting the charging state of said storage battery means;

controlling, via said braking control means, said engine, said first motor, and said second motor based on the detected charging state of said storage battery means, to thereby apply a braking force to said drive shaft; and

regulating the charging state of said storage battery means to be within a predetermined range.--

--25. A method of controlling a power output apparatus, for outputting power to a drive shaft, having an engine with an output shaft, a motor with a rotating shaft, a second motor, and three shaft-type power input/output means having three shafts respectively linking said engine and said drive shaft, said method comprising:

inputting and outputting power to and from said rotating shaft;

inputting and outputting power, via said three shaft-type power input/output

means, to and from a residual one shaft, based on predetermined powers input to and

output from any two shafts among said three shafts;

Application No. Reissue of U.S. Patent No. 5,914,575 Issued June 22, 1999

supplying and receiving an electrical energy, from a storage battery means, required for inputting and outputting power to and from said motor;

controlling, using a braking control means, said engine and said motor,

based on a charging state of said storage battery means, in order to enable a braking force
to be applied to said drive shaft;

inputting and outputting power, from a second motor, to and from said output shaft of said engine, in addition to said motor working as a first motor;

supplying and receiving an electrical energy, from said storage battery

means, required for inputting and outputting power to and from said second motor;

controlling said engine, said first motor, and said second motor, using the

braking control means, in order to enable a braking force to be applied to said drive shaft;

detecting a charging state of said storage battery means using a charging

state detection means, wherein controlling said engine, said first motor, and said second motor is based on the charging state of said storage battery means detected by said charging state detection means; and

regulating the charging state of said storage battery means detected by said charging state detection means to be within a predetermined range.--

REMARKS

Claims 1-25 are pending. Claims 3, 5, 8, 9, 14, 17 and 19 are amended and claims 22-25 are added. Claim 3 is a combination of claims 1 and 3; claim 5 is a combination of claims 1 and 5; claim 8 is a combination of claims 1, 6, 7 and 8; claim 9 is a combination of claims 1, 6 and 9; claim 14 is a combination of claims 1, 6 and 14; claim 17 is a combination of claims 1, 15, 16 and 17; and claim 19 is a combination of claims 1, 15 and 19. Added claim 22 is directed to the subject matter of Figure 30; col. 27, line 51